

Two stage progressive gas burners

RS 34-44 MZ



- Two stage progressive gas burners

RS 34-44 MZ burners series covers a firing range from 44 to 550 kW, and it has been designed for use in low or medium temperature hot water boilers, hot air or steam boilers, diathermic oil boilers.

Operation is "two stage progressive"; the burners are fitted with a microprocessor-based burner safety control box which supplies indication of operation and diagnosis of fault cause.

The elevated performance of the fans and combustion head, guarantee flexibility of use and excellent working at all firing rates.

The exclusive design ensures reduced dimensions, simple use and maintenance. Optimization of sound emissions is guaranteed by the special design of the air suction circuit and by incorporated sound proofing material. A wide range of accessories guarantees elevated working flexibility.

Guidelines for installation of burners in conformity to EU Regulation:

A RIELLO burner (Heat Generator), where it is matched with a water-based boiler (Heater Housing) with a nominal output ≤ 400 kW, providing heat for heating purposes and heat to deliver sanitary hot water, can be installed:

- With boilers (heater housings) already in service in the field, for replacement of identical products, in conformity to Article 1, paragraph 2, point (G) of the EU Regulation No. 813/2013;
- With boilers (heater housings) on a new installation, if they have emissions complying with the requirement of Annex II, paragraph 4 of the EU regulation No. 813/2013.

TECHNICAL DATA


Description	Heat output natural gas		Total electrical power kW	Electric power supply		Certification	Note	Code
	kW	Nm ³ /h		Ph/V/Hz	V/Hz			
MODELS FOR STANDARD OPERATION (FS1: ONE STOP EVERY 24 HOURS)								
RS 34 MZ TC FS1	44/130-390	4.5/13-39	0.6	1/230/50-60	230/50-60	CE-0085BR0381	(1)	3789010
RS 34 MZ TL FS1	44/130-390	4.5/13-39	0.6	1/230/50-60	230/50-60	CE-0085BR0381	(1)	3789011
RSP 34 TC FS1	44/130-390	4.5/13-39	0.6	1/230/50-60	230/50-60	CE-0085BR0381	(1)	20008266
RS 44 MZ TC FS1	80/200-550	8/20-55	0.7	1/230/50-60	230/50-60	CE-0085BR0381	(1)	3789110
RS 44 MZ TL FS1	80/200-550	8/20-55	0.7	1/230/50-60	230/50-60	CE-0085BR0381	(1)	3789111
RS 44 MZ TC FS1	80/200-550	8/20-55	0.8	3/400/50-60	230/50-60	CE-0085BR0381	(1)	3789140
RS 44 MZ TL FS1	80/200-550	8/20-55	0.8	3/400/50-60	230/50-60	CE-0085BR0381	(1)	3789141

Net calorific value of natural gas (G20): 10 kWh/Nm³.

The burners comply with 2016/426/EU Regulation, 2014/30/EU - 2014/35/EU - 2006/42/EC Directives and EN 676 Standard.


(1) Model with plug and socket.

FIRING RATES




Useful firing rates for choosing the burner
 1st stage operation range
 Test conditions conforming to EN676
 Temperature: 20 °C
 Pressure: 1013.5 mbar
 Altitude: 0 m a.s.l.


OVERALL DIMENSIONS



Description	A mm	D mm	E mm	F - F(1) mm	H mm	I mm	L mm	M mm	N mm	O mm	V mm
RS 34 MZ	442	422	508	216-351	140	305	138	1"½	84	780	177
RS 44 MZ	442	422	508	216-351	152	305	138	1"½	84	780	177



Description	D1 mm	D2 mm	Ø mm
RS 34 MZ	160	224	M8
RS 44 MZ	160	224	M8





Description	X (1) mm	Y mm	Z mm	Net weight kg
RS 34 MZ	1000	485	500	32
RS 44 MZ	1000	485	500	33



(1) Dimension with standard and extended head.

PRESSURE LOSS DIAGRAMS

MB SERIES GAS TRAIN



VGD SERIES GAS TRAIN



Please note: the diagrams indicate the minimum gas pressure drops of the burners equipped with the gas trains to be used (approved according to the EN 676 standard); in order to obtain the minimum pressure required at gas train inlet, combustion chamber counterpressure (expressed in mbar) must be added to this value.

— Combustion head + gas train
 - - - Combustion head

GAS TRAINS

Description (1)	Code	Note	Ø Gas train	Valve seal control (2)	VPS kit code (3)	Burner-gas train adapter (4)	
						RS 34 MZ	RS 44 MZ
MB SERIES ONE STAGE GAS TRAIN							
MB 405/1-RT 20	3970500*		Rp 3/4"	-	3010123	3000824	
MB 407/1-RT 20	3970553*		Rp 3/4"	-	3010123	3000824	
MB 407/1-RT 52	3970599*		Rp 3/4"	-	3010123	3000824	
MB 407/1-RSM 20	3970229*		Rp 3/4"	-	3010123	3000824	
MB 410/1-RT 52	3970258*		Rp 1" 1/4	-	3010123	3010124	
MB 410/1-RT 20	3970554*		Rp 3/4"	-	3010123	3000824	
MB 410/1-RT 52	3970600*		Rp 3/4"	-	3010123	3000824	

GAS

LIGHT OIL

DUAL FUEL






HEAVY OIL

Description (1)	Code	Note	Ø Gas train	Valve seal control (2)	VPS kit code (3)	Burner-gas train adapter (4)	
						RS 34 MZ	RS 44 MZ
MB 410/1-RSM 20	3970230*		Rp ¼"	-	3010123	3000824	
MB 412/1-RT 52	3970256*		Rp 1" ½	-	3010123	□	□
MB 412/1-RT 20	3970144*		Rp 1" ½	-	3010123	□	□
MB 412/1 CT RT 20	3970197**		Rp 1" ½	◆	◆	□	□
MB 412/1-RSM 20	3970231*		Rp 1" ½	-	3010123	□	□
MB 415/1-RT 30	3970180*		Rp 1" ½	-	3010123	□	□
MB 415/1 CT RT 30	3970198**		Rp 1" ½	◆	◆	□	□
MB 415/1-RT 52	3970250*		Rp 1" ½	-	3010123	□	□
MB 415/1 CT RT 52	3970253**		Rp 1" ½	◆	◆	□	□
MB 415/1-RSM 30	3970232*		Rp 1" ½	-	3010123	□	□
MB 420/1-RT 30	3970181*		Rp 2"	-	3010123	3000822	
MB 420/1 CT RT 30	3970182**		Rp 2"	◆	◆	3000822	
MB 420/1-RT 52	3970257*		Rp 2"	-	3010123	3000822	
MB 420/1 CT RT 52	3970252**		Rp 2"	◆	◆	3000822	
MB 420/1-RSM 30	3970233*		Rp 2"	-	3010123	3000822	
MB 420/1 CT RSM 30	3970234**		Rp 2"	◆	◆	3000822	
VGD SERIES ONE STAGE GAS TRAIN							
VGD 50/1-RT 122	20137718*		Rp 2"	-	3010123+ 20186306	3000822	
VGD 50/1 CT RT 122	20169190**		Rp 2"	◆	◆	3000822	
VGD 65/1-FT 122	20140762*	(5)	DN65	-	3010123	●	3000826+ 3000822
VGD 65/1 CT FT 122	20169191**	(5)	DN65	◆	◆	●	3000826+ 3000822

- (1) Please refer to "GAS TRAIN DESIGNATION".
 (2) The valve seal control device is compulsory (conforming to EN 676) on gas trains to burners with a maximum output over 1200 kW.
 (3) Valve leak detection control device. Supplied separately from the gas train (see "GAS TRAIN ACCESSORIES" paragraph for both 50 Hz and 60 Hz codes).
 (4) The code indicates the adapter necessary for "burner-gas train connection (see "GAS TRAINS ACCESSORIES)".
 (5) Ø in = DN65; Ø out = DN80
 * 230V/50Hz - 220V/60Hz electrical supply.
 ** 230V/50Hz electrical supply.
 NOTE: for further information, refer to section "GAS TRAINS FOR BURNERS".

- Key to symbols:
 - Gas train not equipped with leak detection control device; this device can be ordered separately - see VPS column - and installed later.
 ◆ Gas train equipped with leak detection control device.
 □ Additional adapter not necessary, the gas train may be connected directly to the burner.
 ● Gas train not available or not suitable for the matching to the burner.

ACCESSORIES

Drawing	Burner model	Specification	Note	Code
	RS 34 MZ RS 44 MZ	EXTENDED HEAD KIT Burners standard head can be transformed into "extended head" versions by using the special kit. Here the kits available for the various burners are listed, showing the original and the extended lengths. Standard head length = 216 mm - Extended head length = 351 mm		3010428 3010429
	All models	CONNECTION FLANGE KIT A kit is available for use where the burner opening on the boiler is of excessive diameter.		3010138
	All models	SPACER KIT If burner head penetration into the combustion chamber needs reducing, varying thickness spacers are available. Spacer thickness S = 110 mm		3010095
	All models	CONTINUOUS VENTILATION KIT If the burner requires continuous ventilation in the stages without flame, a special kit is available.		3010449
	All models	POST-VENTILATION KIT To prolong ventilation after opening of thermostats chain, a special kit is available. Post-ventilation time 20s.		3010452

GAS

LIGHT OIL

DUAL FUEL

HEAVY OIL

Drawing	Burner model	Specification	Note	Code
	All models	SOUND PROOFING BOX If noise emission needs reducing even further, sound-proofing boxes are available. When a lower "B" dimension is required, it is available the box support kit code 20065135 which allows to reduce it at the fixed dimension of 55 mm. The sound-proofing boxes are not suitable for outdoor use. Box type: C1/3 Dimensions: A = 650 mm, B (min-max) = 372-980 mm, C = 110 mm D = 690 mm, E = 770 mm Average noise reduction according to EN 15036-1 Standard = 10 dB(A).		3010403
	All models	GROUND FAULT INTERRUPTER KIT A ground fault interrupter kit is available as a safety device in case of electrical system fault.		3010448
	All models	VOLT FREE CONTACT KIT A volt free contact kit is available for installation onto the burner. It can be used for a remote interface between burner operating signals. Every burner can be equipped with a single kit for a remote check of the flame presence signal and the burner lockout indication.		3010419
	RS 34 MZ	LPG KIT For burning LPG gas, a special kit is available to be fitted to the combustion head on the burner. Kit code for standard and extended head.		3010423
	RS 44 MZ	Kit code for standard and extended head.		3010424
	RS 34 MZ	TOWN GAS KIT For burning town gas, a special kit is available to be fitted to the combustion head on the burner. Kit code for standard and extended head.	(1)	3010502
	RS 44 MZ	Kit code for standard and extended head.	(1)	3010503
	RS 34 MZ	VIBRATION REDUCTION KIT The kit allow you to improve flame stability in some applications, where the boiler/flue assembly is liable to resonate. Natural gas version.	(2)	20098750
	RS 34 MZ	LPG version.	(3)	20098753
	RS 44 MZ	Natural gas version.	(2)	20098746
	All models	GAS MAX PRESSURE SWITCH If necessary a gas max pressure switch kit is available and connectable to the burner electrical wiring trough plugs & sockets system.	(4)	3010418
	All models	HOURS COUNTER KIT To measure the burner working time a hours counter kit is available.		3010450
	All models	PROTECTION KIT (ELECTROMAGNETIC INTERFERENCES) When the burner is installed in a room particularly subject to electromagnetic interference (signals emitted over 10 V/m) due for example to INVERTER presence or in systems where the lengths of the thermostat connections is over 20 meters, this specific protection kit is available as an interface between the thermostatic controls and the burner.		3010386
	All models	PC INTERFACE KIT To connect the control box to a personal computer for the transmission of operation, fault signals and detailed service information, an interface adapter with PC software are available.		3002719

- (1) Without CE certification.
- (2) CE approved.
- (3) CE approval on field is required.
- (4) Connectable to the burner electrical wiring through plugs and sockets system.

STATE OF SUPPLY

Monoblock forced draught gas burner with two stage operation, fully automatic, made up of:

- Air suction circuit with sound proofing material
- High performance fan with straight blades
- Air damper for air flow setting and butterfly valve for regulating fuel output on 1st and 2nd stage controlled by a servomotor with variable cam
- Starting motor at 2800 rpm, single-phase / 220-230V / 50-60Hz or three-phase / 380-400V / 50-60Hz
- Combustion head, that can be set on the basis of required output, fitted with:
 - stainless steel end cone, resistant to corrosion and high temperatures
 - ignition electrodes
 - ionisation probe
 - gas distributor
 - flame stability disk
- Exclusive patented HCS (Housing Cooling System) with high thermal insulation and air circulation with continuous air volume refresh for an active cooling system and avoid heat transfer to the electrical component housing
- Minimum air pressure switch stops the burner in case of insufficient air quantity at the combustion head
- Microprocessor-based burner safety control box, with diagnostic functions
- Plug and socket for electrical connections accessible from the external of the cover
- Burner on/off selection switch
- 1st - 2nd stage manual switch
- Flame inspection window
- Slide bars for easier installation and maintenance
- Protection filter against radio interference
- IP X0D (IP 40) electric protection level.

STANDARD EQUIPMENT

- 1 gas train flange
- 1 flange gasket
- 4 screws for fixing the flange
- 1 thermal screen
- 4 screws for fixing the burner flange to the boiler
- 3 plugs for electrical connection (RS 34-44 MZ single-phase)
- 4 plugs for electrical connection (RS 44 MZ three-phase)
- Instruction handbook for installation, use and maintenance
- Spare parts catalogue.